

SealArm PS -P

(Formerly known as MYK SEAL PS P)

Two Part Polysulphide Sealant,
Pouring Grade



TECHNICAL DATA SHEET

Product Description

SealArm PS–P is a two pack Polysulphide based, tough flexible durable with strong adhesive sealant and is a pourable version, basically used for movement joints in concrete and pavements

Uses

- Sealing of expansion, contraction & construction joints in building structure such as Basements, subways, retaining walls, floors, external walls, roof terraces & ceilings especially structural expansion joint running through the ceiling.
- Sealing of dynamic structural cracks
- Sealing of water retaining structure joints such as Water tank, reservoir, dams, canals, and water treatment plant.
- Sealing of joints in traffic areas such as Bridges, roads and car parking areas

Features and Benefits

- UV Resistant
- Good Weather ability
- Flame and fuel resistant
- Excellent Flexibility and movement tolerance
- Good resistance to chemicals and hydrocarbons

Application Method

Mixing of SealArm PS -P:

The reweighed components base and hardener have to be mixed individually with a mechanical stirrer before the two are mixed together. Then add the entire contents of hardener to the base container and mix it for 3 minutes by using a mechanical mean until a homogeneous mix is obtained.

Application:

The mixed SealArm PS –P can be poured directly from the mixing container. Pour into the joint to the required level. Finally strip of the masking tape that has been used.



SealArm PS -P

(Formerly known as MYK SEAL PS P)

Two Part Polysulphide Sealant,
Pouring Grade

Consumption

Coverage:
Sealant Requires in Kgs $\frac{W \times D \times L}{1000} = \text{Kgs}$

W – Joint Width in Mtr
D – Sealant Depth in Mtr
L – Joint Length

Packaging

4 Kg Pack

Storage and Shelf Life

Store in cool dry place
12 months from date of manufacturing

Health & Safety

SealArm PS –P should be applied with gloves and care should be taken to see that it doesn't fall on screen or eyes. Splashes on t eyes have to be immediately washed with plenty of water and medical advice has to be taken.

MYK arment

TECHNICAL DATA SHEET

Product Categories Available



Legal Note

The information, and, in particular, the recommendations relating to the application and end-use of MYK Arment products, are given in good faith based on MYK Arment current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with MYK Arment's recommendations. In practice, the difference in materials, substrates and actual site conditions are such that no warranty in respect of merchant ability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. the user of the product must test the product's suitability for the intended application & purpose. MYK Arment reserves the right to change the properties of its products. the proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request.